



Model 6000

Multi-Function Telephone Network Analyzer

FEATURES/KEY BENEFITS

- Diagnostic and fault location functions in one instrument** – Integrated testing system enables the technician to diagnose and locate faults with one easy to use, high quality instrument.
- Diagnostic Test Package** – Identify conditions on the line that can adversely affect service using the following diagnostic tools:
 - Multi-Meter – Measure AC volts, DC volts, foreign battery, resistance and insulation resistance.
 - Pair Quality Tests – Measure loop current, noise metallic, power influence and longitudinal balance.
- Fault Location Test Package** – Restore existing service quicker or reclaim unused lines for new service with accurate fault location tools:
 - Time Domain Reflectometer (TDR)** – Accurately locate opens, shorts, water in cable, bad splices and cable damage with the same full-function TDR found in Riser Bond's stand-alone instruments.
 - Resistance Fault Locator (RFL)** – Three test modes. Locate resistance faults on a pair or on a single conductor.
 - Stress TDR** – This exclusive feature enhances the instrument's ability to locate faults due to moisture in the cable.
 - Open/Capacitance Meter** – Measure capacitance to the end of the pair or locate fault caused by an open circuit.
- Ease-of-Use Features** – The soft-key menu's intuitive left-to-right operation guides the technician through logical testing steps to diagnose and locate faults. Most tests are performed using the same connection to the line.
- Auto-Test and Fault Analysis Functions** – Press the Auto-Test key to perform a series of basic diagnostic tests. The Fault Analysis function will then suggest the appropriate fault location tool to use to most effectively locate the problem.
- SUPER-STORE Waveform Data Storage** – Analyze TDR waveforms in a more convenient time or place. The instrument also stores Auto-Test records.
- WAVE-VIEW Software** – View, manipulate, print and archive TDR waveforms on your computer. Document plant, certify new builds, and store waveforms for later comparisons.
- Optional Oscillator and Probe** – One unassisted technician working at a distance from the exchange can disconnect a customer's service, identify the cable pair, open and close the circuit, and reconnect the customer after desired tests are complete.
- Large LCD Display** – Test results and interpretive information are presented in an easy to read format on a screen that is larger than those found on many competitive units.



Radiodetection
 Dielectric Technologies
 Pearpoint • Riser Bond

Model 6000

Integrated test solution

Product Specifications

Physical Dimensions

<i>Main instrument without carrying case & accessories:</i>	
Height:	6.93 inches (176 mm)
Width:	10.71 inches (272 mm)
Depth:	3.15 inches (80 mm)
Weight:	4.8 pounds (2.2 kg)
<i>Main instrument with carrying case and accessories:</i>	
Height:	7.80 inches (198 mm)
Width:	11.18 inches (284 mm)
Depth:	7.0 inches (178 mm)
Weight:	7.9 pounds (3.6 kg)

Power

Internal:	Rechargeable, 7.2 V Nickel metal hydride battery pack
External:	12 VAC or VDC, 1250mA power supply
Operating Time:	Greater than 5 hours, continuous without backlight

Environment

Operating temperature:	0 \uparrow C (+32 \uparrow F) to +50 \uparrow C (+122 \uparrow F)
Storage temperature:	-20 \uparrow C (-4 \uparrow F) to +60 \uparrow C (+140 \uparrow F)
Humidity:	95% maximum relative humidity, non-condensing IEC 68-2-3
Vibration:	IEC 68-2-6
Shock (Bump):	IEC 68-2-29, 40g, 6ms, 1000 shocks in each axis
Drop:	IEC 68-2-27, 1m free fall, packaged in carry case
Moisture rating:	IP 54

Display

320 x 240 dot-matrix, liquid crystal display (LCD) with CCFL backlighting

Multi-Meter

<i>DC Voltage:</i>	0 to 400V
Resolution:	0.1V
Accuracy:	1% \pm 0.1V
<i>AC Voltage:</i>	0 to 400V
Resolution:	0.1V
Accuracy:	2% \pm 0.1V
<i>Foreign Battery:</i>	2 to 400V
Resolution:	0.1V
Accuracy:	1% \pm 0.1V
<i>Resistance:</i>	
0 to 1999.9W	
Resolution:	0.1W
Accuracy:	0.2% \pm 0.2W
2KW to 10KW	
Resolution:	1W
Accuracy:	0.2% \pm 1W

Insulation Resistance

Voltages:	50V/100V/250V/500V
0W to 9.99MW	
Resolution:	0.01MW
Accuracy:	2% \pm 0.01MW
10MN to 99.9MW	
Resolution:	0.1MW
Accuracy:	4%
100MN to 999MW	
Resolution:	1MW
Accuracy:	10%

Open/Capacitance Meter

0 to 1000 ft (0 to 100 m)	
Resolution:	1 ft (0.1 m)
Accuracy:	2% \pm 3 ft (1 m)
1000 ft to 10,000 ft (100 m to 1,000 m)	
Resolution:	10 ft (1 m)
Accuracy:	\pm 3%
10,000 ft to 100,000 ft (1000 m to 10,000 m)	
Resolution:	100 ft (10 m)
Accuracy:	\pm 5%
100,000 ft to 150,000 ft (10,000 m to 50,000 m)	
Resolution:	1000 ft (100 m)
Accuracy:	\pm 8%
0 to 9.99nF	
Resolution:	0.01nF
Accuracy:	2% \pm 0.06nF
10.0 to 99.9nF	
Resolution:	0.1 nF
Accuracy:	\pm 3%
100 to 999nF	
Resolution:	1 nF
Accuracy:	\pm 5%
1000 to 2000nF	
Resolution:	1 nF
Accuracy:	\pm 8%

Pair Quality

<i>Loop Current:</i>	0 to 120mA
Resolution:	0.1mA
Accuracy:	5% \pm 0.2mA
<i>Noise Metallic:</i>	0 to 50 dBmC
Resolution:	1 dB
Accuracy:	\pm 2 dB
<i>Power Influence:</i>	40 to 100dBmC

Resolution:	1 dB
Accuracy:	\pm 2 dB
<i>Longitudinal Balance:</i>	40 to 62dB
Resolution:	1 dB
Accuracy:	\pm 2 dB

Time Domain Reflectometer (TDR)

loaded and non-loaded cable	
Maximum Ranges:	
<i>Live waveform:</i>	
63,700 feet (19,400 meters) at 99.0% VOP	
38,600 feet (11,700 meters) at 60.0% VOP	
Range varies with VOP. Maximum testable cable length varies with pulse width and cable type.	
<i>Stored waveform:</i>	
11,900 ft (3,600.0 m) at 99.0% VOP	
7,200 ft (2,200.0 m) at 60.0% VOP	
Range varies with VOP.	
Horizontal Resolution:	
Up to 2,000 ft (610 m): <.25 ft (.07 m) at 99.0% VOP	
<.07 ft (.02 m) at 30.0% VOP	
Over 2,000 ft (610 m)	1 ft (.1 m) at any VOP
Vertical Resolution:	14 bits with 137 dots displayed
Vertical Sensitivity:	Greater than 65 dB
Output Signal:	Pulse widths of 2ns, 25ns, 100ns, 500ns, 1.5 μ s, 4.4 μ s and 330 μ s
Output Balance:	Variable, from 80W to 120W
Velocity of Propagation:	Two user-selectable display formats.
VOP (%):	Non-loaded cable: 30.0% to 99.0%
	Loaded cable: 0.8% to 20.0%
V/2:	Non-loaded cable: 147.5 to 486.9 ft/ μ s (45.0 to 148.4 m/ μ s)
	Loaded cable: 3.9 to 98.4 ft/ μ s (1.2 to 30.0 m/ μ s)

Input Protection: 400 VAC or VDC up to 60 Hz
Distance Accuracy: Accuracy will vary with cable VOP and cable type. +/- .5 ft (.15 m) plus +/- .01% of reading

Software Noise Filters

Standard: 8x, 50/60 Hz



Optional: 4x, 8x, 16x, 32x, 64x, 128x, 50/60 Hz

Resistance Fault Locator (RFL)

Location Range:	0 to 150 kft (0 to 45 km)
Resistance fault range:	0 to 50MW
Accuracy	
3-Wire Test:	\pm 0.25% of DTS plus \pm 0.4W
4-Wire Test:	\pm 0.25% of DTS plus \pm 0.25W
Kupfmuller Test:	\pm 1.0% of DTS plus \pm 1W
Storage	
Standard:	8 Auto Test and TDR waveform records
Optional:	32 Auto Test and TDR waveform records

Riser Bond Oscillator and Probe

Communications for: short pair, open pair, exchange connect, disconnect, pair identification tone

Accessories:

Standard: Operator's Manual, 12VDC charger, nylon carry/ accessory bag, shoulder strap, 2 sets telco connection leads plus ground lead, pair shorting strap, VOP card.
Optional: Extended waveform storage, extended TDR noise filters, Extended Warranty.

Technological advances allow changes in specifications and/or components. Changes may be made without notification.

MAINTAINING THE CONNECTION

At Riser Bond Instruments, our first commitment is to you, our customer.

We start with product. Riser Bond builds our entire line of high-performance test equipment to meet your unique needs. And then we back them all with training, technical support, and the most comprehensive customer service and warranty in the industry.

When you choose Riser Bond, you have decades of product design knowledge and field experience inside every one of our state-of-the-art test instruments, and a guarantee of expert service after the sale. Riser Bond... maintaining the connection.

Radiodetection
RR#2 Box 756
Brighton Commerce Center
Bridgton
Maine 04009, U.S.A.
Telephone (207) 647-9495
U.S. Toll Free (870) 247-3797



Radiodetection
Dielectric Technologies
Pearpoint • Riser Bond

ISO 9001 REGISTERED